Downlights





OVERVIEW

The Series 900 is an IP65 ceiling recessed LED downlight available in two different sizes. Designed for use in secure healthcare applications, the Series 900 is an anti-ligature downlight, with output choices from 1100, 2000 and 3000 lumens. A choice of colour temperatures also provide excellent flexibility in this challenging application, alongside dimming and emergency options.

FEATURES

- · Anti-Ligature design to prevent self harming
- IP65 and IK10 rating for the harshest of environments.
- 2 size and 3 output options, make it suitable for a myriad of applications
- 100 to 122 delivered Lumens per Watt
- Premium European drivers from VS, Osram and Tridonic
- · Emergency plug and play options

OPTIONS

- 3000 or 4000K
- 2 size options 195mm & 237mm
- 1100, 2000 or 3000 lumens
- · Dimming control via Dali or wireless via Bluetooth
- Emergency plug and play in self-test or manual versions















T: 01282 476600 | E: info@photoniclighting.co.uk
Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH


www.photoniclighting.co.uk


SERIES 900

Downlights





PRODUCT DIMENSIONS





PHOTOMETRIC





T: 01282 476600 | E: info@photoniclighting.co.uk
Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH

www.photoniclighting.co.uk

SERIES 900

Downlights



PRODUCT SPECIFICATION

900 - (SZ) - (LM) - (CCT) - (OP) - W - (CTR) - (EM)

| Size (SZ) | | |
|-----------|-------------|--|
| Code | Description | |
| 237 | Ø237mm | |
| 195 | Ø195mm | |

| Lumen Output (LM) | | |
|-------------------|----------------|--|
| Code | Description | |
| 110 | 1100lm (9.5W) | |
| 200 | 2000lm (17.5W) | |
| 300 | 3000lm (30.5W) | |

| Correlated Colour Temperature (CCT) | | |
|-------------------------------------|-----------------|--|
| Code | Description | |
| 830 | 3000K 80 CRI | |
| 840 | 4000K 80 CRI | |
| TW | Tuneable White* | |

*Only available in 2000 & 3000lm and Bluetooth Casambi

| Beam angle (OP) | | |
|-----------------|------------------------------------|--|
| Code | Description | |
| 60 | 60° (with clear lens)*195mmØ only | |
| 50 | 50° (with clear lens) | |
| 40 | 40° (with clear lens) *237mmØ only | |
| 0 | Opal | |

| Control (CTR) | | |
|---------------|-------------------|--|
| Code | Description | |
| N | Non dim | |
| D | DALI | |
| RD | Retractive Dim | |
| BC | Bluetooth Casambi | |

| Emergency (EM) | | |
|----------------|----------------------|--|
| Code | Description | |
| L3 | 3W Lithium | |
| SL3 | 3W Self test lithium | |
| DE3 | DALI 3W emergency | |

OPTIONS





T: 01282 476600 | E: info@photoniclighting.co.uk
Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH

www.photoniclighting.co.uk