Controls





OVERVIEW

Series 620 is a DALI controller which seamlessly integrates wired DALI drivers into a Casambi system. The DALI luminaires appear as luminaires as individual devices within the Casambi network. Series 620 also supports industry standards such as DALI D4i, DALI DT6 and DALI DT8. The unit also has an integrated 130mA bus power supply to allow for DALI operation without any extra equipment. The IP65 version comes contained within an IP65 plastic enclosure with cable glands for mains and DALI wiring.

FEATURES

- IP20
- Input 100-277VAC
- Dali output 12-15VDC, 130mA
- Ta -20°C to 50°C
- Radio transceiver 2402-2480 MHz, +8 dBm

OPTIONS

- IP65 option with additional enclosure
- 3 different device sizes 16, 32 & 64.









T: 01282 476600 | E: info@photoniclighting.co.uk Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH


www.photoniclighting.co.uk


SERIES 620

Controls



PRODUCT DIMENSIONS





PHOTOMETRIC

PRODUCT SPECIFICATION

Size (SZ)	
Code	Description
16	Up to 16 DALI driver devices
32	Up to 32 DALI driver devices
64	Up to 64 DALI driver devices

IP Rating (IP)	
Code	Description
IP20	IP20 rated
IP65	IP65 rated within enclosure

OPTIONS



T: 01282 476600 | E: info@photoniclighting.co.uk
Unit 1 Boran Court, Network 65, Hapton, Burnley BB11 5TH

www.photoniclighting.co.uk